

FBS 300 P5

Office
Application

Page 07



Product description

Recessed aesthetic luminaires suitable for use with 2 / 3 X PL-L 36W and 2 X 18 W PL-L compact fluorescent lamps.

Features

- Housing made of single piece powder coated CRCA sheet steel accommodating all electrical accessories pre-wired up to a terminal block.
- The perimeter of the luminaire is provided with perforations of 2 mm diameter with 3 mm orthocyclic pitch to add aesthetic appeal.
- A reflector assembly, made of metalized polystyrene paralite PS type louvers.

Applications

- Representatives offices and conference rooms
- Small offices and general open plan offices
- Corridors and staircases
- Recreational areas, sport halls, restaurants, cafeterias
- Department stores, shops and boutiques

Mounting Type

Recessed luminaires

Installation

- Resting on T-bar of false ceiling
- Suspension via hooks on chains


Compliances

- IP 20
- Class I


Technical data

Type	For lamp	Nominal voltage (V)	Main current (A)	Nominal power factor
FBS300 M 3XPL-L36W IC P5	3XPL-L36W	240	0.65	0.9
FBS300 M 2XPL-L36W IC P5	2XPL-L36W	240	0.46	0.9
FBS300 M 3XPL-L36W EBP P5	3XPL-L36W	240	0.3	0.98
FBS 300 2XPLL 36W P5 EBT	2XPL-L36W	240	0.46	0.98

FBS 300 3xPL-L 36W



FBS 300 2xPL-L 18W



Technical Drawing



Ordering data

Type	Ordering data	Quantity per box	Dimensions (mm)	Net weight (kg)	Gross weight (kg)	Volume (m3)
FBS300 M 3XPL-L36W IC P5	919015087130	2	660x660x170	5.6	11.8	0.074
FBS300 M 2XPL-L36W IC P5	919015088291	2	660x660x170	6.4	13.4	0.074
FBS300 M 3XPL-L36W EBP P5	919015088391	2	660x660x170	4.7	10	0.074
FBS 300 2XPLL 36W P5 EBT 236	919015810177	2	660x660x170	4.5	9.6	0.074

Dimmable version with 0-10 v dc Analog dimming and Digital Dali 'DALI' are available on request.

