

DN 622

Retail
Application

Page 21

Office
Application

Page 07



Product description

Recessed Downlights type DN 622 is suitable for use with GLS 100W (maximum) incandescent lamps. To be used in non-ventilated false ceilings. DN 622 has a symmetric beam.

Features

- Ceiling ring made of aluminium, pressure die-cast.
- MS frame with two adjustable mounting clamps. The mounting clamps can be adjusted according to the ceiling thickness.
- Reflector made of satin finish brightened and anodised aluminium. The reflector is held in position by a pair of leaf springs.

Applications

- Representative offices
- Conference rooms
- Reception, corridors and staircases
- Recreational areas, sport halls, restaurants, cafeterias
- Department stores, shops and boutiques

Mounting Type

Downlights and Accents

Installation

Designed for recessed mounting on false ceilings. This luminaire can be mounted with the help of flexible mounting clamps.

Compliances



- IP 20
- Class I

Technical data

Type	For lamp	Nominal voltage (V)	Main current (A)	Nominal power factor
DNS622	1 x A60 100W WH	240	0.43	1.00

Ordering data

Type	Ordering data	Quantity per box	Dimensions (mm)	Net weight (kg)	Gross weight (kg)	Volume (m3)
DNS 622 1xA60 100W WH	919215000095	12	575 x 390 x 460	0.45 x 12	8.30	0.103

IP 20 

Technical Drawing



