

# Opalite - TCS 019

Office  
Application

Page 07



# Product description

Functional glare free luminaires for surface mounting in ceilings suitable for TLD / TL fluorescent lamps.

## Features

- Housing made of CRCA sheet steel, powder coated gray accommodating all electrical accessories pre-wired up to a terminal block.
- Cover made of opal acrylic.
- Designed for surface mounting on ceilings.

## Applications

- Small offices
- Reception and public service areas
- Recreational areas (restaurants, cafeterias)
- Shops

## Mounting Type

Surface mounted luminaires

## Installation

Provision for suspension through Ø19mm conduit or direct on surface.

## Compliances

- IP 20


**Technical data**

Type	For lamp	Nominal voltage (V)	Main current (A)	Nominal power factor
TCS019 1XTL-D18W I O	1xTL-D18W	240	0.23	0.44
TCS019 1XTL-D36W I O	1xTL-D36W	240	0.23	0.44
TCS019 2XTL40W I O	2xTL-D40W	240	0.46	0.44
TCS019 2XTL-D18W IC O	2xTL-D18W	240	0.23	0.9
TCS019 2XTL-D36W IC O	2xTL-D36W	240	0.46	0.9
TCS019 1XTL-D36W IC O	1xTL-D36W	240	0.23	0.9
TCS 019 2XTLD 36W EBT	2xTL-D36W	240	0.32	0.98
TCS 019 1XTLD 36W EBT	1xTL-D36W	240	0.16	0.98



IP 20



TCS 019 2xTL-D 18W



TCS 019 1xTL-D 36W



TCS 019 2xTL-D 36W



Technical Drawing

**Ordering data**

Type	Ordering data	Quantity per box	Dimensions (mm)	Net weight (kg)	Gross weight (kg)	Volume (m3)
TCS019 1XTL-D18W I O	441536074171	4	700x410x310	1.2	6.8	0.088
TCS019 1XTL-D36W I O	919015079121	4	1350x170x209	1.85	9.1	0.048
TCS019 2XTL40W I O	919015071121	4	1360x325x232	3	13.4	0.102
TCS019 2XTL-D18W IC O	919015071081	4	700x410x310	2	9.5	0.088
TCS019 2XTL-D36W IC O	919015071122	4	1360x325x232	3	13.4	0.102
TCS019 1XTL-D36W IC O	919015071129	4	1350x170x209	1.88	9.2	0.048
TCS 019 2XTLD 36W EBT	919015810213	4	1360x325x232	2	9.4	0.102
TCS 019 1XTLD 36W EBT	919015810212	4	1350x170x209	2	9.7	0.048

Dimmable version with 0-10 v dc Analog dimming and Digital Dali 'DALI' are available on request.

